

**Revision Date:** 04/18/2007

**Issue date:** 04/18/2007

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b> SPDBNDR H4800 PART A 40 LB PAIL <b>Product type:</b> Acrylics <b>Company address:</b> Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067	<b>Item No. :</b> 83047 / IDH No. 398451 <b>Region:</b> United States <b>Contact Information:</b> Telephone: 860.571.5100 Emergency telephone: 860.571.5100 Internet: www.loctite.com
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Methyl methacrylate 80-62-6	30-60	50 ppm TWA 100 ppm STEL	100 ppm TWA 410 mg/m <sup>3</sup> TWA	50 ppm
Hydroxyalkyl methacrylate 868-77-9	10-30	None	None	3 ppm (ceiling)
Polyethylene based rubber Proprietary	10-30	None	None	None
Methacrylic acid 79-41-4	1-5	20 ppm TWA	None	None
2,6-Di-t-butyl-p-cresol 128-37-0	1-5	2 mg/m <sup>3</sup> TWA	None	None
Talc 14807-96-6	0.1-1	2 mg/m <sup>3</sup> TWA	= 20 mppcf TWA	50 ppm

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**Physical state:** Liquid  
**Color:** White Opaque  
**Odor:** Sharp

**HMIS:**

<b>HEALTH:</b>	2*
<b>FLAMMABILITY:</b>	3
<b>PHYSICAL HAZARD:</b>	1
<b>Personal Protection:</b>	See Section 8

**WARNING:** FLAMMABLE LIQUID AND VAPOR.  
 CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION  
 HARMFUL IF SWALLOWED.  
 MAY CAUSE ALLERGIC SKIN REACTION.

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

**Potential Health Effects**

<b>Inhalation:</b>	Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.
<b>Skin contact:</b>	Irritating to skin. May cause allergic skin reaction.
<b>Eye contact:</b>	Vapors may irritate eyes. Contact with eyes will cause irritation.
<b>Ingestion:</b>	May be harmful if swallowed. Ingestion causes irritation and effects similar to inhalation.

**Existing conditions aggravated by exposure:** Eye, skin, and respiratory disorders.

**See Section 11 for additional toxicological information.**

## 4. FIRST AID MEASURES

<b>Inhalation:</b>	Remove to fresh air. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if symptoms occur.
<b>Eye contact:</b>	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Keep individual calm. Obtain medical attention.

## 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	14°C (58°F)    Setflash Closed cup
<b>Autoignition temperature:</b>	Not available
<b>Flammable/Explosive limits-lower %:</b>	Not available
<b>Flammable/Explosive limits-upper %:</b>	Not available
<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special fire fighting procedures:</b>	None
<b>Unusual fire or explosion hazards:</b>	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
<b>Hazardous combustion products:</b>	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Hydrogen cyanide. Hydrogen chloride. Acids. Aldehydes. Alcohols. Toxic fumes. Acrid smoke and fumes. Irritating organic vapors.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	Prevent product from entering drains or open waters.
<b>Clean-up methods:</b>	Remove all ignition sources. Ensure adequate ventilation. Soak up with inert absorbent. Store in a closed container until ready for disposal.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material.
<b>Storage:</b>	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. For safe storage, store at or below 32°C (90°F).
<b>Incompatible products:</b>	Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Engineering controls:</b>	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
<b>Respiratory protection:</b>	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
<b>Skin protection:</b>	Chemical resistant, impermeable gloves. Nitrile gloves.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields.

**See Section 2 for exposure limits.**

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	White Opaque
<b>Odor:</b>	Sharp
<b>Vapor pressure:</b>	28 mmHg @20°C (68° F)
<b>pH:</b>	Not applicable
<b>Boiling point/range:</b>	Greater than 38°C (100°F)
<b>Melting point/range:</b>	Not available
<b>Specific gravity:</b>	1.02
<b>Vapor density:</b>	Greater than 1
<b>Evaporation rate:</b>	Faster than ether
<b>Solubility in water:</b>	Slight
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>VOC content:</b>	2.60%; 26.0 grams/liter (Adhesive and Activator mixed)

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable.
<b>Hazardous polymerization:</b>	May occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Hydrogen cyanide. Hydrogen chloride. Acids. Aldehydes. Alcohols. Carbon tetrachloride. Styrene. Acrolein. Acetophenone. Ethylbenzene. Cumene. 4-Vinyl cyclohexene. Phenols. Irritating organic vapors. Toxic fumes. Smoke.
<b>Incompatibility:</b>	Oxidizing agents. Reducing agents. Acids. Bases.
<b>Conditions to avoid:</b>	See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10). Do not mix in batches greater than 100 grams (0.220 pounds) unless you plan to use immediately.

## 11. TOXICOLOGICAL INFORMATION

### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Methyl methacrylate 80-62-6	No	No	No
Hydroxyalkyl methacrylate 868-77-9	No	No	No
Polyethylene based rubber Proprietary	No	No	No
Methacrylic acid 79-41-4	No	No	No
2,6-Di-t-butyl-p-cresol 128-37-0	No	No	No
Talc 14807-96-6	No	No	No

### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Methyl methacrylate 80-62-6	Allergen, Irritant, Kidney, Liver, Nervous System, Respiratory, Mutagen
Hydroxyalkyl methacrylate 868-77-9	Allergen, Irritant
Polyethylene based rubber Proprietary	No Target Organs
Methacrylic acid 79-41-4	Allergen, Corrosive, Irritant
2,6-Di-t-butyl-p-cresol 128-37-0	Mutagen, Irritant
Talc 14807-96-6	Some evidence of carcinogenicity, Lung, Irritant

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: D001: Ignitable. D019: Carbon tetrachloride.

## 14. TRANSPORT INFORMATION

### U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Adhesives  
Hazard class or division: 3  
Identification number: UN 1133  
Packing group: II  
Exceptions: Consumer Commodity ORM-D (Not more than 5 L)  
Marine pollutant: None

### International Air Transportation (ICAO/IATA):

Proper shipping name: Adhesives  
Hazard class or division: 3  
Identification number: UN 1133  
Packing group: II  
Exceptions: May Qualify as Consumer Commodity ID8000 (Not more than 500 ml)

### Water Transportation (IMO/IMDG):

Proper shipping name: Adhesives  
Hazard class or division: 3  
Identification number: UN1133  
Packing group: II  
Marine pollutant: None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None above reporting de minimus.  
CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard, Fire  
CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methyl Methacrylate (CAS# 80-62-6) .

California Proposition 65: This product contains a chemical known to the State of California to cause cancer.

### Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.  
WHMIS hazard class: B.2, D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2, 15

**Prepared by:** Kyra Kozak Woods, Manager, Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.