



# LOCTITE<sup>®</sup> Paint Stripper

January 2007

## PRODUCT DESCRIPTION

LOCTITE<sup>®</sup> Paint Stripper provides the following product characteristics:

<b>Technology</b>	Solvent cleaner
<b>Chemical Type</b>	Methylene Chloride
<b>Appearance</b>	Grey to Off White spray
<b>Components</b>	One component - requires no mixing
<b>Viscosity</b>	Very low
<b>Cure</b>	Not applicable
<b>Application</b>	Paint stripper
<b>Specific Benefit</b>	<ul style="list-style-type: none"> <li>• Works in minutes</li> <li>• Removes paint and varnish from carved surfaces without scraping or damage</li> <li>• Safe on metal, wood and plaster</li> <li>• Does not contain CFC</li> </ul>

LOCTITE<sup>®</sup> Paint Stripper is an aerosol that removes paint, varnish and glues from metals, wood and plaster. Other typical applications include cleaning paint spills, removing floor lines, decals, labels, and contact cements.

## TYPICAL PROPERTIES

Specific Gravity @ 25 °C 1.3  
Flash Point - See MSDS

## Material Compatibility

Not for use on plastic, linoleum or synthetic fabrics. If left in contact with Aluminum, a reaction may take place causing pitting. Flush off with shop solvent for 15 to 20 minutes.

## GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a lubricant for chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).**

## Directions for use

1. Hold can in an upright position 25 to 30 cm from area to be sprayed.
2. Spray area to be stripped - the heavier the coat, the better.
3. Allow sprayed area to set for 10 minutes. Remove paint or varnish with a putty knife.
4. Hose parts with water or wipe clean with a rag.
5. Repeat application if necessary.

## Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

## Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

**Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.**

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

## Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$   
 $\text{kV/mm} \times 25.4 = \text{V/mil}$   
 $\text{mm} / 25.4 = \text{inches}$   
 $\mu\text{m} / 25.4 = \text{mil}$   
 $\text{N} \times 0.225 = \text{lb}$   
 $\text{N/mm} \times 5.71 = \text{lb/in}$   
 $\text{N/mm}^2 \times 145 = \text{psi}$   
 $\text{MPa} \times 145 = \text{psi}$   
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$   
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$   
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$   
 $\text{mPa}\cdot\text{s} = \text{cP}$

## Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0