



LOCTITE[®] Pro Strength Degreaser

January 2007

PRODUCT DESCRIPTION

LOCTITE[®] Pro Strength Degreaser provides the following product characteristics:

Technology	Solvent cleaner
Chemical Type	Petroleum distillate
Appearance	Clear liquid ^{LMS}
Components	One component - requires no mixing
Viscosity	Very low
Cure	Not applicable
Application	Degreasing
Specific Benefit	<ul style="list-style-type: none"> • Quickly dissolves grease, oil and dirt • Cleans iron, steel, aluminum, magnesium and copper • Not harmful to metal, rubber, plastic or concrete • Rinses off easily with water • VOC compliant

LOCTITE[®] Pro Strength Degreaser is a highly concentrated, self-emulsifying solvent degreaser specially formulated to quickly cut and remove grease, oil and dirt on all types of equipment. The product also inhibits rust and corrosion. Typical applications include, cleaning and degreasing automobile engines, industrial equipment, farm equipment, lawn mowers, garage floors and tools.

TYPICAL PROPERTIES

Specific Gravity @ 25 °C 1.53
Flash Point - See MSDS

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected with a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

Directions for use

1. Provide adequate ventilation.
2. Warm up motor for easier cleaning and turn off. Remove air filter. Protect carburetor and distributor.
3. Shake can thoroughly before use. **Note:** There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
4. Holding 20 to 25 cm from the surface, press the nozzle and apply an even coat of product on the surface. Allow to soak 10 to 20 minutes depending upon the amount of soil buildup. Repeat cleaning process if required.
5. Rinse with strong jet of water. Collect run-off with plastic sheet placed under the motor. Idle motor to dry.

Clean-up

1. Dispose plastic sheet in accordance with state and local regulations.
2. Clean hands with hand cleaners.

Loctite Material Specification^{LMS}

LMS dated December 04, 2001. Test reports for each batch are available for the indicated properties. LMS test reports include selected QC test parameters considered appropriate to specifications for customer use. Additionally, comprehensive controls are in place to assure product quality and consistency. Special customer specification requirements may be coordinated through Henkel Quality.

Storage

The product is classified as flammable and must be stored in an appropriate manner in compliance with relevant regulations. Do not store near oxidizing agents or combustible materials. Store product in the unopened container in a dry location. Storage information may also be indicated on the product container labelling.

Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel**

Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0