



LOCTITE[®] Pro Strength Varnish Remover

January 2007

PRODUCT DESCRIPTION

LOCTITE[®] Pro Strength Varnish Remover provides the following product characteristics:

Technology	Solvent based
Chemical Type	Aromatic ketone blend
Appearance	Clear liquid
Cure	Non-curing
Application	Cleaner
Specific Benefit	<ul style="list-style-type: none"> • Cuts and removes grease and varnish • Improves engine performance • Oxygen sensor safe • OEM certified • VOC compliant

LOCTITE[®] Pro Strength Varnish Remover is a blend of solvents specifically formulated to dissolve and clean the residue deposited on carburetors and chokes during the normal operation of gasoline engine powered equipment. Typical applications include carburetors, manual and automatic chokes, linkages, heat risers and PCV valves.

TYPICAL PROPERTIES

Specific Gravity @ 25 °C 0.74
Flash Point - See MSDS

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

Directions for use

1. Provide adequate ventilation.
2. Shut engine off.
3. Protect painted surfaces thoroughly from over-spray, as LOCTITE[®] Pro Strength Varnish Remover will attack the paint.
4. Shake can thoroughly before use.
5. **NOTE:** This product does not require a ball agitator.
6. Best results are obtained when the product is at room temperature.
7. Holding can 20 to 25 cm from the surface for open area cleaning, or 12 cm using the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.
8. **Carburetor:** Spray carburetor inside and out covering all parts. Repeat application if necessary.
9. **Automatic Choke:** Mark indicator plate before removing. Spray directly into choke housing on spring and other parts. Repeat application if necessary. Wipe dry. Reinstall parts with indicator plate in original position.

Clean-up

1. Clean hands with hand cleaners.

Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

Storage

The product is classified as flammable and must be stored in an appropriate manner in compliance with relevant regulations. Do not store near oxidizing agents or combustible materials. Store product in the unopened container in a dry location. Storage information may also be indicated on the product container labelling.

Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from

domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0